

Technical Specifications: R-Evo Smart® S

GENERAL INFORMATION

Manufacturer	OPTIKON 2000 S.p.A. Via del Casale di Settebagni, 13 - 00138 Rome - Italy
Model	R-Evo Smart® S
Ref	111010
Regulatory compliance	93/42/EEC Medical Device Directive (MDD)
Technical standards	EN60601-1 EN60601-1-2 EN60601-2-2 EN80601-2-58

ENVIRONMENTAL SPECIFICATIONS

Storage and transport	Temperature -10°C - +70°C, humidity 10% -100% (non-condensing), atmospheric pressure 500 - 1060 hPa
Operating	Temperature range +10°C - +35°C, humidity 30%-75%, atmospheric pressure 900 - 1060 hPa (for maximum vacuum); 810 - 1060 hPa (for vacuum up to 500 mmHg)

ELECTRICAL SPECIFICATIONS

Input voltage	100-240 VAC
Frequency	50/60 Hz
Power supply	200 VA
Fuses	100-240 Volt: T3.15AH 250V

COMPRESSED AIR SPECIFICATIONS

Air inlet pressure	500 - 800 kPa (72 - 116 PSI; 5 - 8 bar)
Air consumption	32 Normal litre/min

IRRIGATION

Fluid delivery	Microprocessor-controlled active infusion or gravity fed (ocular pressure determined by the height of irrigation source)
Valves	Pinch valve
Control	Footpedal

ASPIRATION

Aspiration pump types	Peristaltic and Venturi
Actuating medium	Peristaltic pump: rollers Venturi pump: air from an external source at 500-800 kPa (72-116 PSI; 5-8 bar)
Default vacuum level	User programmable
Available vacuum range	5 - 650 mmHg
Default flow rate	User programmable
Available flow rate range	1-65 cc/min (peristaltic only)
Vacuum rise time	Peristaltic: adjustable on 25 levels (0.5s-12s) Venturi: adjustable on 2 levels (fast/slow)
Aspiration mode	Peristaltic: fixed or linear flow rate combined with fixed or linear vacuum Venturi: fixed or linear vacuum
System feedback	Vacuum sensor, measuring the vacuum in the aspiration line
Control	Footpedal

ANTERIOR VITRECTOMY

Handpiece type	Pneumatically powered guillotine cutter
Default cutting rate	User programmable
Available cutting rate	60 - 5,000 cuts/min 120 - 10,000 cuts/min with Twedge™ technology
Pneumatic drive	Pressurized air from an external source
Cutting mode	Fixed or linear
Control	Footpedal

DIATHERMY

Type	Bipolar generator - the generator stops when the RF power supply is not needed
Operating frequency	2 MHz
Nominal power	9 W (200 Ohm load)
No load max. voltage	100 V
Default power	User programmable
Available range	5% - 100%
Handpiece type	Bipolar forceps, diathermy brush, endodiathermy probes
Diathermy cable	Bipolar, 75 Ohm, 200V max, steam autoclavable
Control	Linear control of the DIATHERMY power via footpedal

PHACOEMULSIFICATION

Handpiece type	Piezoelectric available with four or six crystals
Frequency	Approx. 40 kHz
Tip stroke	5µm steps up to 100µm
Power control	Fixed or linear control of U/S power via footpedal
U/S mode	Continuous, pulsed (with preset duty cycle), single-multiple-continuous burst
Occlusion mode	Autolimit, HD pulse
Timer U/S	0:00 - 9:59 min - Equivalent Phaco Time (EPT)

EQUIPMENT CLASSIFICATION ACCORDING TO EN 60601-1

Type of protection against electric shock	Class I
Degree of protection against electric shock:	
Diathermy	Type BF, floating at high and low frequencies
U/S	Type B
Vitrectomy	Type BF
Degree of protection against water (system unit)	IPX0
Degree of protection against water (footpedal)	IPX8
Degree of safety in the presence of a flammable anaesthetics	Not suitable

NOTE:

- 1) The weight and dimensions shown are approximate.
- 2) Specifications are subject to change without notice.

